

TENDERING SPECIFICATIONS FOR DOOR AND WINDOW FRAMES SCRIGNO FOR INTERIORS

SCRIGNO GOLD BASE FOR PLASTERED WALLS

Metal frame in aluzinc sheet metal, model "SCRIGNO GOLD BASE", with internal opening 54/69/89 mm for interior partition walls made from 6/8/10/12 cm hollow brickwork blocks with an overall finished thickness of 90/105/125/145 mm, suitable for containing one door (single-door model) or two doors (double-door model), sliding, rigid, concealed, with a maximum unit weight of 120 kg.

Clear opening size: cm x cm.

Original Scigno door and window frames are always accompanied by a Certificate of Authenticity. Therefore Scigno offers a lifetime anti corrosion warranty to Aluzinc parts and guarantee of 20 years on the components of the frame and hangers.

SCRIGNO GOLD BASE FOR PLASTERBOARD WALLS

Metal frame in aluzinc sheet metal, model "SCRIGNO GOLD BASE", with internal opening 54/69 mm for interior partition walls in plasterboard made from 75/100 mm profiles with an overall finished thickness of 100/125 mm, suitable for containing one door (single-door model) or two doors (double-door model), sliding, rigid, concealed, with a maximum unit weight of 120 kg.

Clear opening size: cm x cm.

Original Scigno door and window frames are always accompanied by a Certificate of Authenticity. Therefore Scigno offers a lifetime anti corrosion warranty to Aluzinc parts and guarantee of 20 years on the components of the frame and hangers.

≈≈≈≈

Scigno S.p.A. has submitted several of its frames for interior use for testing by the Istituto Giordano, to determine their effective performance. In particular, "**Mechanical tests for sliding door accessories**" were carried out on the **Scigno Gold sliding system (track and hanger)** in accordance with the UNI EN 1527:2000 standard. For further details, the Istituto Giordano "Test Report" dated 08/09/2006 should be consulted.