

TENDERING SPECIFICATIONS FOR DOOR AND WINDOW FRAMES SCRIGNO FOR INTERIORS

SCRIGNO REMIX FOR PLASTERWORK

Metal frame in aluzinc sheet metal, model "SCRIGNO REMIX", with internal opening of 69 mm, for interior partition walls made from 8 cm hollow brickwork blocks with an overall finished thickness of 105 mm, suitable for containing two rigid glass doors, sliding, disappearing and moved by dragging, with a thickness of 105 mm and a maximum weight of 80 kg each. The specific characteristics of the REMIX frame make it indispensable to be used in combination with its own finished door or with its specific hardware fittings.

Clear opening size: cm x..... cm

Original Scrigno door frames are always accompanied by a Certificate of Authenticity and by a **lifelong guarantee** against perforations of the aluzinc caused by corrosion and a guarantee of 20 years on frame components and the hanger assembly.

≈≈≈≈

Scrigno S.p.A. has submitted several of its frames for interior use for testing by the Istituto Giordano, to determine their effective performance. In particular, "**Mechanical tests for sliding door accessories**" were carried out on the **Scrigno Gold sliding system (track and hanger)** in accordance with the UNI EN 1527:2000 standard. For further details, the Istituto Giordano "Test Report" dated 08/09/2006 should be consulted.