

## TENDERING SPECIFICATIONS FOR DOOR AND WINDOW FRAMES SCRIGNO FOR INTERIORS

### SCRIGNO GOLD CONTATTO FOR PLASTERED WALLS

Metal frame in aluzinc sheet metal, model "SCRIGNO GOLD CONTATTO", with internal opening 54/69/89 mm for interior partition walls made from 6/8/10/12 cm hollow brickwork blocks with an overall finished thickness of 90/105/125/145 mm, suitable for containing one panel (single-panel model) or two panels (double-panel model) sliding, rigid, concealed, with a maximum unit weight of 120 kg.

Clear opening size: ..... cm x ..... cm.

Original Scrigno door and window frames are always accompanied by a Certificate of Authenticity. Therefore Scrigno offers a lifetime anti corrosion warranty to Aluzinc parts and guarantee of 20 years on the components of the frame and hangers.

### SCRIGNO GOLD CONTATTO FOR PLASTERBOARD WALLS

Metal frame in aluzinc sheet metal, model "SCRIGNO GOLD CONTATTO", with internal opening 54/69 mm for interior partition walls in plasterboard made from 75/100 mm profiles with an overall finished thickness of 100/125 mm, suitable for containing one panel (single-panel model) or two panels (double-panel model) sliding, rigid, concealed, with a maximum unit weight of 120 kg.

Clear opening size: ..... cm x ..... cm.

Original Scrigno door and window frames are always accompanied by a Certificate of Authenticity. Therefore Scrigno offers a lifetime anti corrosion warranty to Aluzinc parts and guarantee of 20 years on the components of the frame and hangers.

≈≈≈≈

Scrigno S.p.A. has submitted several of its frames for interior use for testing by the Istituto Giordano, to determine their effective performance. In particular, "**Mechanical tests for sliding door accessories**" were carried out on the **Scrigno Gold sliding system (track and hanger)** in accordance with the UNI EN 1527:2000 standard. For further details, the Istituto Giordano "Test Report" dated 08/09/2006 should be consulted.