News Mirr Swing Glass Door





In the Essential range, Scrigno has created a swing glass door flush with the wall.

With its refined style, clean lines and imperceptible profile, it aligns perfectly with the frame, creating a fusion between door and environment.

The door, with single or double glass, 5 cm thick, is available in different types of glass: clear, bronzed, etched, smoky grey, extra clear transparent, extra clear etched, smoked reflex and lacquered back. There is also a wide choice of colours for the internal aluminium perimeter structure.

The Mirr Swing glass door can be supplied in both single and double sheet solutions, to best meet all living needs and exploit the different types of glass.

The light weight of the glass and the transparency, which allows the light to filter through, make the Mirr Swing Glass door a real furnishing accessory able to give a touch of refinement to the environment.

Mirr Swing Glass Door

Measurements and Opening directions

Commercial Opening L x H	Door Lp= L+20 x Hp= H+5	Notes
600 x 1800÷2200	620 x 1805÷2205	3 Hinges
700 x 1800÷2200	720 x 1805÷2205	
750 x 1800÷2200	770 x 1805÷2205	
800 x 1800÷2200	820 x 1805÷2205	
900 x 1800÷2200	920 x 1805÷2205	
1000 x 1800÷2200	1020 x 1805÷2205	
600 x 2210÷2700	620 x 2215÷2705	4 Hinges
700 x 2210÷2700	720 x 2215÷2705	
750 x 2210÷2700	770 x 2215÷2705	
800 x 2210÷2700	820 x 2215÷2705	
900 x 2210÷2700	920 x 2215÷2705	
1000 x 2210÷2700	1020 x 2215÷2705	

KEY

L= Commercial Opening Width
H= Commercial Opening Height

Lp= Door width Hp= Door height

Single Mirr glass door directions Pull Lh Pull Rh Pull Lh Push Rh Push Lh Push Lh Push Lh Push Lh

Glass finishes

GLASSES



LAQUERS



* Snow white (25) not available in double-sided glass version

The sample colours shown here are approximate.

Any colour tolerances and finishes are to be considered acceptable.



TEMPERED GLASS Tempered glass sheet, 4 mm thick, in compliance with UNI EN 12150 standard.

MIRROR GLASS